



# Leo

Circular suspension with double ring with opal diffuser. Thanks to the double ring, one 800 mm with direct light and the other 600 mm with indirect light, this suspension guarantees high levels of illuminance. Available only in 3000K version, white or black finishing. It has a source emission of about 7050 lm. Design and size make Leo an elegant decorative and furnishing element, its performance makes it very versatile. Leo adapts to all environments, even large ones. Perfect for reception (reception, cash desks, hall) and suitable for general lighting of shops, bars, restaurants and meeting rooms, also suitable for the home environment.

|                                      |   |
|--------------------------------------|---|
| <b>Artikelnummer</b>                 | <b>6993-32-966</b>  |
| <b>Typ</b>                           | Pendelleuchte   |
| <b>EAN</b>                           | 8019282553502   |
| <b>Zolltarif</b>                     | 94051190  |
| <b>Farbe</b>                         | Schwarz   |
| <b>Material</b>                      | Aluminium / Opalweiß Diffusor   |
| <b>IP</b>                            | IP20  |
| <b>IK</b>                            | 07  |
| <b>Isolierklasse</b>                 |    |
| <b>Operating ambient temperature</b> | 0°C +35°C   |
| <b>Artikelmaße</b>                   | MAX 2000mm Ø800mm - 2.9kg   |
| <b>Verpackungsmaße</b>               | 80x830x830mm - 4.6kg  |
|                                      | <b>Bestückung 1</b>   |
| <b>Bestückung</b>                    | LED Eingebaut   |
| <b>LED Merkmale</b>                  | SMD   |
| <b>Lumen der Lichtquelle</b>         | 7050 lm   |
| <b>Lumen des Artikels</b>            | 4900 lm   |
| <b>Farbtemperatur</b>                | Warm white 3000K  |
| <b>Diffusor</b>                      | Diffused beam   |
| <b>Typischer CRI</b>                 | >80   |
| <b>Energieklasse</b>                 |  |
|                                      | <b>Elektrische Spezifikationen 1</b>  |
| <b>Eingangsspannung</b>              | 220 - 240V AC 50/60 Hz  |
| <b>Gesamtabsorbierte Leistung</b>    | 65W   |
| <b>Treiber</b>                       | Inklusiv  |
| <b>Leistungsfaktor</b>               | >0,9  |
| <b>Steuerungssystem</b>              | DALI  |

