

Fabas Luce S.p.a.
Via Luigi Talamoni 75,
20861 BRUGHERIO MB - ITALY
Tel. +39 039 890691
Fax. +39 039 2142208
info@fabasluce.it - www.fabasluce.it

## Lucas

Small compact LED ceiling light. Indoor use. Ceiling or wall mounted. Square-shaped aluminum body. Available in white or anthracite finishing. It is equipped with an opal polycarbonate diffuser that distributes the light evenly. Thanks to its versatility, it is suitable for residential and commercial environments, creating welcoming atmospheres.

| Code                          | 3601-84-102                  |
|-------------------------------|------------------------------|
| Туре                          | Ceiling lamp                 |
| Designer                      | S.T. Fabas Luce              |
| Eancode                       | 8019282518563                |
| Customs tariff                | 94051190                     |
| Color                         | White                        |
| Material                      | Metal and methacrylate frame |
| IP                            | IP20                         |
| IK                            | 04                           |
| Insulation Class              |                              |
| Smartluce                     | Compatible                   |
| Operating ambient temperature | +5°C + 35°C                  |
| Years of warranty             | 2                            |
| Item Dimensions               | 350x350x80mm - 2.7kg         |
| Packaging Dimensions          | 400x400x125mm - 3.1kg        |
|                               | Light Source 1               |
| Light source                  | LED Included                 |
| LED Characteristics           | SMD                          |
| Light Source Lumen            | 4160 lm                      |
| Item Lumen                    | 2275 lm                      |
| Color Temperature             | Warm white 3000K             |
| Minimum CRI                   | >80                          |
| Energy Efficiency Class       | E C                          |
|                               | Electrical specifications 1  |
| Input Voltage                 | 220 - 240V AC 50/60 Hz       |
| Total Absorbed Power          | 48W                          |
| Driver                        | Included                     |
| Control System                | Dimmerabile a taglio di fase |





