

Fabas Luce S.p.a.
Via Luigi Talamoni 75,
20861 BRUGHERIO MB - ITALY
Tel. +39 039 890691
Fax. +39 039 2142208
info@fabasluce.it - www.fabasluce.it

Ravello 595X595

Ravello is a recessed lighting fixture, with a 600x600mm modular structure. It can be installed on the ceiling, suspended and clip-in, with special accessories. Ravello is a LED panel with innovative traits, characterized by great versatility of use, equipped with a backlight optical system that eliminates progressive yellowing of the screen over time. The microprismatic screen guarantees a UGR<19 factor, equipped with LED 3000K or 4000K 42W, CRI ?90.

Code	6520-04-001			
Туре	Recessed lamp			
Designer	S.T. Fabas Luce			
Eancode	8019282544845			
Customs tariff	94054239			
Color	White			
Material	Metal frame / Opal prismatic diffuser			
IP	IP40			
IK	04			
Insulation Class				
Operating ambient temperature	-20°+50°C			
Years of warranty	3			
Item Dimensions	595x595x35mm			
	Light Source 1			
Light source	LED Built-in		32	
LED Characteristics	SMD			
Number of LEDs	72			
Light Source Lumen	4814 lm			
Item Lumen	3800 lm		595	
Color Temperature	Natural white 4000 K		Ω.	
Optics	Prismatic			
Typical CRI	90			
Minimum CRI	>90			595
Luminous Flux Maintenance	>54.000h L80 B50		,	370
UGR	<19			
Energy Efficiency Class	♠ E	10:	0° Gamma Angles 180	1200
	Electrical specifications 1	90	.	90°
Input Voltage	220 - 240V AC 50/60 Hz			
Total Absorbed Power	42W	75		75°
Driver	Included	60		60°
Power Factor	>0,9			50
Control System	On/Off	45		45°
			30° 15° 0'	50 ¢d/klm