

Fabas Luce S.p.a.
Via Luigi Talamoni 75,
20861 BRUGHERIO MB - ITALY
Tel. +39 039 890691
Fax. +39 039 2142208
info@fabasluce.it - www.fabasluce.it

Ravello 595X595

Ravello is a recessed lighting fixture, with a 600x600mm modular structure. It can be installed on the ceiling, suspended and clip-in, with special accessories. Ravello is a LED panel with innovative traits, characterized by great versatility of use, equipped with a backlight optical system that eliminates progressive yellowing of the screen over time. The microprismatic screen guarantees a UGR<19 factor, equipped with LED 3000K or 4000K 36W, CRI ?90.

Code	6520-04-005			
Туре	Recessed lamp			
Designer	S.T. Fabas Luce			
Eancode	8019282544616			
Customs tariff	94054239			
Color	White			
Material	Metal frame / Opal prismatic diffuser			
IP	IP40			
IK	04			
Insulation Class				
Operating ambient temperature	-20°+50°C			
Years of warranty	3			
Item Dimensions	595x595x35mm			
	Light Source 1			
Light source	LED Built-in		93	
LED Characteristics	SMD			
Number of LEDs	72			
Light Source Lumen	4150 lm			
Item Lumen	3287 lm		595	
Color Temperature	Natural white 4000 K		Ω Ω	
Optics	Prismatic			
Typical CRI	90			
Minimum CRI	>90		595	
Luminous Flux Maintenance	>54.000h L80 B50		070	
UGR	<19			-
Energy Efficiency Class	A E G E	105°	2° Gurma Angles 180°	120°
	Electrical specifications 1	90°		90°
Input Voltage	220 - 240V AC 50/60 Hz			
Total Absorbed Power	36W	75°		75°
Driver	Included	60°	300	60°
Power Factor	>0,9		450	
Control System	On/Off	45°		45°
			130	d/klm 30°