



Skilos

Skilos recessed backing is a lighting fixture with a 600x600 mm modular structure. Provided with an optical system which allows excellent visual comfort, the microprismatic screen guarantees a UGR<19 factor. Equipped with the latest generation of very high efficiency LEDs, 4000K natural light, CRI >90. The IP65 degree of protection is guaranteed both on the visible side and on the recessed side. Particularly suitable for operating, aseptic, chemical and food premises.

| | |
|--------------------------------------|---|
| Code | 6524-04-705 |
| Type | Recessed lamp |
| Designer | S.T. Fabas Luce |
| Eancode | 8019282552703 |
| Customs tariff | 94054239 |
| Color | White |
| Material | Metal frame / Clear prismatic diffuser |
| IP | IP65 |
| IK | 04 |
| Insulation Class |  |
| Operating ambient temperature | -20°C +45°C |
| Years of warranty | 5 |
| Item Dimensions | 595x595x75mm - 5.9kg |
| Packaging Dimensions | 640x640x80mm - 6.6kg |
| Light Source 1 | |
| Light source | LED Built-in |
| LED Characteristics | SMD |
| Light Source Lumen | 4222 lm |
| Item Lumen | 3231 lm |
| Color Temperature | Natural white 4000 K |
| Optics | Prismatic |
| Minimum CRI | >90 |
| UGR | <19 |
| Energy Efficiency Class |  |
| Electrical specifications 1 | |
| Input Voltage | 220 - 240V AC 50/60 Hz |
| Total Absorbed Power | 25W |
| Driver | Included |
| Power Factor | > 0.9 |
| Control System | DALI/Push/On-Off |

