

Fabas Luce S.p.a.
Via Luigi Talamoni 75,
20861 BRUGHERIO MB - ITALY
Tel. +39 039 890691
Fax. +39 039 2142208
info@fabasluce.it - www.fabasluce.it

Ermes

Suspension LED light which has been designed for use in all ERMES system profiles. This illuminator can be combined with a series of metal diffusers of different shapes and colors or a series of borosilicate glass diffusers of different sizes and finishing in summary, this luminaire combined with the wide range of diffusers represents a versatile and high quality lighting solution, suitable for different environments.

Code	6525-56-016
Туре	Suspension lamp
Designer	S.T. Fabas Luce
Eancode	8019282557463
Customs tariff	94059900
Color	Black
Material	Aluminum frame
IP	IP20
IK	04
Insulation Class	
Operating ambient temperature	-20°C + 35°C
Years of warranty	3
Item Dimensions	185xMax 1380mm Ø50mm - 0.3kg
Packaging Dimensions	240x140x115mm - 0.4kg
	Light Source 1
Light source	LED Built-in
LED Characteristics	
ZZD Gridiadtoriotico	SMD
Light Source Lumen	SMD 750 lm
Light Source Lumen	750 lm
Light Source Lumen Item Lumen	750 lm 479 lm
Light Source Lumen Item Lumen Color Temperature	750 lm 479 lm CCT (2700K-3000K-4000K)
Light Source Lumen Item Lumen Color Temperature Optics	750 lm 479 lm CCT (2700K-3000K-4000K) Diffused beam
Light Source Lumen Item Lumen Color Temperature Optics Minimum CRI	750 lm 479 lm CCT (2700K-3000K-4000K) Diffused beam >80
Light Source Lumen Item Lumen Color Temperature Optics Minimum CRI	750 lm 479 lm CCT (2700K-3000K-4000K) Diffused beam >80
Light Source Lumen Item Lumen Color Temperature Optics Minimum CRI Energy Efficiency Class	750 lm 479 lm CCT (2700K-3000K-4000K) Diffused beam >80 A E Electrical specifications 1
Light Source Lumen Item Lumen Color Temperature Optics Minimum CRI Energy Efficiency Class Input Voltage	750 lm 479 lm CCT (2700K-3000K-4000K) Diffused beam >80 A Electrical specifications 1 48V DC





