

Fabas Luce S.p.a. Via Luigi Talamoni 75, 20861 BRUGHERIO MB - ITALY Tel. +39 039 890691 Fax. +39 039 2142208 info@fabasluce.it - www.fabasluce.it

Ermes

Thanks to its compact design, the 10W ERMES spotlight for 48V profile system is a lighting device designed to be mounted on 48V tracks. This type of spotlight is ideal for highlighting particular areas or objects in an environment. Available with three types of optics, two color temperatures, in either white or black finishing, On-Off and DALI.

| Code | 6525-83-463 | | |
|-------------------------------|-----------------------------|------|-----|
| Туре | Track spotlight | | |
| Eancode | 8019282551164 | | |
| Customs tariff | 94051190 | | |
| Color | Black | | |
| Material | Aluminum frame | | |
| IP | IP20 | | |
| IK | 04 | | |
| Insulation Class | | | |
| Operating ambient temperature | -20°C + 35°C | | |
| Years of warranty | 3 | | |
| Item Dimensions | 185x30mm Ø45mm - 0.2kg | | |
| Packaging Dimensions | 210x115x50mm - 0.3kg | | |
| | Light Source 1 | | |
| Light source | LED Built-in | | |
| LED Characteristics | СОВ | | |
| Light Source Lumen | 770 lm | | |
| Item Lumen | 673 lm | | |
| Color Temperature | Warm White 2700K | | |
| Optics | 32° | | |
| Typical CRI | 90 | | |
| Luminous Flux Maintenance | 50.000h L80 B10 | | |
| Energy Efficiency Class | A G E | | |
| | Electrical specifications 1 | 120° | 0. |
| Input Voltage | 48V DC | 120* | Gan |
| Total Absorbed Power | 10W | 105° | - |
| Driver | Included | 90° | |
| Control System | On/Off | 75° | |
| | | 1 10 | 1 |





