



## Grant 46W

Indoor projector with high efficiency, particularly suitable for illuminating functional areas and architectural lighting. It has a wide range of optics and is available in two color temperatures, 3000K and 4000K, to meet all design requirements. Metal frame. 48V DC appliance with the option of remote power.

|                                      |   |
|--------------------------------------|---|
| <b>Code</b>                          | <b>6835-14-324</b>  |
| <b>Type</b>                          | Indoor Projector  |
| <b>Designer</b>                      | S.T. Fabas Luce   |
| <b>Eancode</b>                       | 8019282083610   |
| <b>Customs tariff</b>                | 94054239  |
| <b>Color</b>                         | White   |
| <b>Material</b>                      | Metal frame   |
| <b>IP</b>                            | IP40  |
| <b>IK</b>                            | 08  |
| <b>Insulation Class</b>              |    |
| <b>Operating ambient temperature</b> | -20°C +50°C   |
| <b>Years of warranty</b>             | 5   |
| <b>Made In</b>                       | Italy   |
| <b>Item Dimensions</b>               | 98x128x128mm - 2.0kg  |
| <b>Packaging Dimensions</b>          | 310x175x135mm - 2.3kg   |
| <b>Light Source 1</b>                |   |
| <b>Light source</b>                  | LED Built-in  |
| <b>LED Characteristics</b>           | Power LED   |
| <b>Light Source Lumen</b>            | 6100 lm   |
| <b>Item Lumen</b>                    | 3775 lm   |
| <b>Color Temperature</b>             | Natural white 4000 K  |
| <b>Optics</b>                        | 21°   |
| <b>Typical CRI</b>                   | 70  |
| <b>Luminous Flux Maintenance</b>     | >60.000 L70 B50   |
| <b>Energy Efficiency Class</b>       |  |
| <b>Electrical specifications 1</b>   |   |
| <b>Input Voltage</b>                 | 48V DC  |
| <b>Total Absorbed Power</b>          | 46W   |
| <b>Driver</b>                        | Not included  |
| <b>Power Factor</b>                  | >0,9  |
| <b>Power Supply Type</b>             | Costant Current   |

