

Fabas Luce S.p.a. Via Luigi Talamoni 75, 20861 BRUGHERIO MB - ITALY Tel. +39 039 890691 Fax. +39 039 2142208 info@fabasluce.it - www.fabasluce.it

Grant 96W

Indoor projector with high efficiency, particularly suitable for illuminating functional areas and architectural lighting. It has a wide range of optics and is available in two color temperatures, 3000K and 4000K, to meet all design requirements. Metal frame. 48V DC appliance with the option of remote power.

| Code | 6835-24-624 | |
|-------------------------------|-----------------------------|--|
| Туре | Indoor Projector | |
| Designer | S.T. Fabas Luce | |
| Eancode | 8019282083726 | |
| Customs tariff | 94054239 | and the second s |
| Color | White | and a company of the second se |
| Material | Metal frame | VO DO |
| IP | IP40 | |
| IK | 08 | |
| Insulation Class | | |
| Operating ambient temperature | -20°C +50°C | |
| Years of warranty | 5 | |
| Made In | Italy | |
| Item Dimensions | 256x95x128mm - 3.5kg | _ |
| Packaging Dimensions | 400x180x230mm - 4.1kg | - 256 |
| | Light Source 1 | |
| Light source | LED Built-in | |
| LED Characteristics | Power LED | - Q. D. 3 |
| Light Source Lumen | 11200 lm | |
| Item Lumen | 6972 lm | - |
| Color Temperature | Natural white 4000 K | |
| Optics | 65° | |
| Typical CRI | 70 | |
| Luminous Flux Maintenance | >60.000 L70 B50 | - |
| Energy Efficiency Class | | 135' Gamma Angles 180' 165' 150' 135' |
| | Electrical specifications 1 | |
| Input Voltage | 48V DC | 120° 800 120° |
| Total Absorbed Power | 96W | 105* 300 105* |
| Driver | Not included | 90. |
| Power Factor | >0,9 | |
| Power Supply Type | Costant Current | 75* 75* |
| | | |