



## Turner Suspension lamp

Modular linear profile in extruded aluminum, with opal or microprismatic polycarbonate diffuser UGR<19. Available in 29W/m, warm white or natural white. Integrated power supply for On/Off and DALI; emergency module available on demand. Suitable to be installed as suspension in unidirectional configuration. Complete with suspension and power cable max 2m.

<b>Code</b>	<b>6847-24-202</b>
<b>Type</b>	Light Line Profiles - Suspension lamp
<b>Designer</b>	S.T. Fabas Luce
<b>Eancode</b>	8019282091424
<b>Customs tariff</b>	94054239
<b>Color</b>	Aluminum
<b>Material</b>	Aluminum frame
<b>IP</b>	IP40
<b>IK</b>	08
<b>Insulation Class</b>	
<b>Operating ambient temperature</b>	-20C° +45°
<b>Years of warranty</b>	5
<b>Made In</b>	Italy
<b>Item Dimensions</b>	77x95xMax 2000mm - 3,950/mtkg

<b>Light Source 1</b>	
<b>Light source</b>	LED Built-in
<b>LED Characteristics</b>	SMD
<b>Number of LEDs</b>	70 LED/mt
<b>Light Source Lumen</b>	3570 lm/m
<b>Item Lumen</b>	2308 lm/m
<b>Color Temperature</b>	Natural white 4000 K
<b>Optics</b>	Prismatic
<b>Typical CRI</b>	85
<b>Minimum CRI</b>	80
<b>Luminous Flux Maintenance</b>	>100.000 h L70 B50
<b>UGR</b>	<19
<b>Energy Efficiency Class</b>	

<b>Electrical specifications 1</b>	
<b>Input Voltage</b>	220 - 240V AC 50/60 Hz
<b>Total Absorbed Power</b>	29W/ml
<b>Driver</b>	Included
<b>Control System</b>	On/Off
<b>Power Supply Type</b>	Costant Current
<b>Driver Output</b>	24V DC
<b>Driver Input</b>	220 - 240 VAC 50/60 Hz

