



Turner Suspension lamp

Modular linear profile in extruded aluminum, with opal or microprismatic polycarbonate diffuser UGR<19. Available in 29W/m, warm white or natural white. Integrated power supply for On/Off and DALI; emergency module available on demand. Suitable to be installed as suspension in unidirectional configuration. Complete with suspension and power cable max 2m.

| | |
|--------------------------------------|---|
| Code | 6847-64-202 |
| Type | Light Line Profiles - Suspension lamp |
| Designer | S.T. Fabas Luce |
| Eancode | 8019282534518 |
| Customs tariff | 94054239 |
| Color | Black |
| Material | Aluminum frame |
| IP | IP40 |
| IK | 08 |
| Insulation Class |  |
| Operating ambient temperature | -20C° +45° |
| Years of warranty | 5 |
| Made In | Italy |
| Item Dimensions | 77x95xMax 2000mm - 3,950/mtkg |

| | |
|----------------------------------|---|
| Light Source 1 | |
| Light source | LED Built-in |
| LED Characteristics | SMD |
| Number of LEDs | 70 LED/mt |
| Light Source Lumen | 3570 lm/m |
| Item Lumen | 2308 lm/m |
| Color Temperature | Natural white 4000 K |
| Optics | Prismatic |
| Typical CRI | 85 |
| Minimum CRI | 80 |
| Luminous Flux Maintenance | >100.000 h L70 B50 |
| UGR | <19 |
| Energy Efficiency Class |  |

| | |
|------------------------------------|------------------------|
| Electrical specifications 1 | |
| Input Voltage | 220 - 240V AC 50/60 Hz |
| Total Absorbed Power | 29W/ml |
| Driver | Included |
| Control System | On/Off |
| Power Supply Type | Costant Current |
| Driver Output | 24V DC |
| Driver Input | 220 - 240 VAC 50/60 Hz |

