




Turner Recessed with frame

Modular linear profile in extruded aluminum, with opal or microprismatic polycarbonate diffuser. Available in 29W/m, warm white or natural white. Integrated power supply for On/Off and DALI; emergency module available on demand. Suitable to be installed recessed (drywall) with frame.

| | |
|--------------------------------------|---|
| Code | 6848-52-222 |
| Type | Light Line Profiles – Recessed with frame |
| Designer | S.T. Fabas Luce |
| Eancode | 8019282107880 |
| Customs tariff | 94054239 |
| Color | White |
| Material | Aluminum frame |
| IP | IP40 |
| IK | 08 |
| Insulation Class |  |
| Hole dimension |  83 x L+23 |
| Operating ambient temperature | -20C° +45° |
| Years of warranty | 5 |
| Made In | Italy |
| Item Dimensions | 93x126mm - 3,950/mtkg |
| | Light Source 1 |
| Light source | LED Built-in |
| LED Characteristics | SMD |
| Number of LEDs | 70 LED/mt |
| Light Source Lumen | 3470 lm/m |
| Item Lumen | 2146 lm/m |
| Color Temperature | Warm white 3000K |
| Optics | Prismatic |
| Typical CRI | 85 |
| Minimum CRI | 80 |
| Luminous Flux Maintenance | >100.000 h L70 B50 |
| UGR | <19 |
| Energy Efficiency Class |  |
| | Electrical specifications 1 |
| Input Voltage | 220 - 240V AC 50/60 Hz |
| Total Absorbed Power | 29W/ml |
| Driver | Included |
| Control System | DALI |
| Power Supply Type | Costant Current |
| Driver Output | 24V DC |
| Driver Input | 220 - 240 VAC 50/60 Hz |

