



Turner Ceiling lamp

Modular linear profile in extruded aluminum, with opal or microprismatic polycarbonate diffuser UGR<19. Available in 29W/m, warm white or natural white. Integrated power supply for On/Off and DALI; emergency module available on demand. Suitable to be installed on the ceiling or wall (vertical and horizontal).

Code	6850-64-222
Type	Light Line Profiles – Ceiling lamp
Designer	S.T. Fabas Luce
Eancode	8019282534464
Customs tariff	94054239
Color	Black
Material	Aluminum frame and polycarbonate
IP	IP40
IK	08
Insulation Class	
Operating ambient temperature	-20C° +45°
Years of warranty	5
Made In	Italy
Item Dimensions	77x95mm - 3,8/mkg
Light Source 1	
Light source	LED Built-in
LED Characteristics	SMD
Number of LEDs	70 LED/mt
Light Source Lumen	3570 lm/m
Item Lumen	2308 lm/m
Color Temperature	Natural white 4000 K
Optics	Prismatic
Typical CRI	85
Minimum CRI	80
Luminous Flux Maintenance	>100.000 h L70 B50
UGR	<19
Energy Efficiency Class	
Electrical specifications 1	
Input Voltage	220 - 240V AC 50/60 Hz
Total Absorbed Power	29W/ml
Driver	Included
Control System	DALI
Power Supply Type	Costant Current
Driver Output	24V DC
Driver Input	220 - 240 VAC 50/60 Hz

