



Zeus 200W

High efficiency floodlight for functional and architectural lighting. Suitable especially for outdoor areas. It has a wide range of optics to meet all design needs. Device made of die-cast aluminum copper free EN AB 44100. Polyester painting QUALICOAT (Class 1), corrosion resistant to salt spray for 28 days, conforms to Standard IEC60092-306. Available in grey color RAL 7040, INOX brackets.

| | |
|--------------------------------------|---|
| Code | 6871-04-624 |
| Type | Outdoor Projector |
| Designer | S.T. Fabas Luce |
| Eancode | 8019282106227 |
| Customs tariff | 94054239 |
| Color | Grey RAL 7040 |
| Material | Aluminum frame |
| IP | IP65 |
| IK | 07 |
| Insulation Class |  |
| Operating ambient temperature | -20°C +35°C |
| Years of warranty | 5 |
| Made In | Italy |
| Item Dimensions | 384x123x319mm - 6.9kg |
| Packaging Dimensions | 420x420x170mm - 7.3kg |

Light Source 1

| | |
|----------------------------------|---|
| Light source | LED Built-in |
| LED Characteristics | SMD |
| Light Source Lumen | 28200 lm |
| Item Lumen | 23410 lm |
| Color Temperature | Natural white 4000 K |
| Optics | 60° |
| Minimum CRI | >80 |
| Luminous Flux Maintenance | 60.000h L70 B50 |
| Energy Efficiency Class |  |

Electrical specifications 1

| | |
|-----------------------------|------------------------|
| Input Voltage | 220 - 240V AC 50/60 Hz |
| Total Absorbed Power | 200W |
| Driver | Included |
| Power Factor | >0,9 |
| Control System | On/Off |

