

Fabas Luce S.p.a. Via Luigi Talamoni 75, 20861 BRUGHERIO MB - ITALY Tel. +39 039 890691 Fax. +39 039 2142208 info@fabasluce.it - www.fabasluce.it

Apache 2 Recessed drive-over ground spotlight. Excellent for creating luminous paths. The light, in addition to aidng orientation, creates an evocative path. Resistant to a static load of up to 780 kg. Application with outer casing supplied. Aluminum structure. Upper front part in AISI 316 stainless steel. Transparent tempered glass diffuser.

| Code                          | 6906-02-414                 |                             |
|-------------------------------|-----------------------------|-----------------------------|
| Туре                          | ground recessed             |                             |
| Designer                      | S.T. Fabas Luce             |                             |
| Eancode                       | 8019282008774               |                             |
| Customs tariff                | 94054239                    |                             |
| Color                         | Stainless steel             |                             |
| Material                      | Stainless steel AISI 316    |                             |
| IP                            | IP67                        |                             |
| к                             | 08                          |                             |
| Insulation Class              |                             |                             |
| Hole dimension                | <b>A</b> 95                 |                             |
| Operating ambient temperature | -20°C +35°C                 |                             |
| Years of warranty             | 3                           |                             |
| Item Dimensions               | 66x66x96mm - 0,60kg         |                             |
| Packaging Dimensions          | 95x95x150mm - 0.7kg         | 8                           |
|                               | Light Source 1              |                             |
| Light source                  | LED Built-in                | 0 53                        |
| LED Characteristics           | СОВ                         | 0 59                        |
| Light Source Lumen            | 480 lm                      |                             |
| Item Lumen                    | 409 lm                      |                             |
| Color Temperature             | Warm white 3000K            |                             |
| Optics                        | 32°                         |                             |
| Minimum CRI                   | >80                         | 30 85                       |
| Energy Efficiency Class       |                             | 120° Gamma Angles 180° 120° |
|                               | Electrical specifications 1 | 105* 800 105*               |
| Input Voltage                 | 220 - 240V AC 50/60 Hz      | 90*                         |
| Total Absorbed Power          | 6,5W                        |                             |
| Driver                        | Included                    | 75°                         |
| Control System                | On/Off                      | 60° 60°                     |
|                               |                             |                             |

çd/kim

15°

15