

Fabas Luce S.p.a.
Via Luigi Talamoni 75,
20861 BRUGHERIO MB - ITALY
Tel. +39 039 890691
Fax. +39 039 2142208
info@fabasluce.it - www.fabasluce.it

Egeo 160W

High efficiency floodlight for functional and architectural lighting. Suitable especially for outdoor areas. It has a wide range of optics to meet all design needs. Device made of die-cast aluminum copper free EN AB 44100. Polyester painting QUALICOAT (Class 1), corrosion resistant to salt spray for 28 days, conforms to Standard IEC60092-306. Available in grey color RAL 7040, INOX brackets.

| Code | 6916-04-724 |
|-------------------------------|-----------------------------|
| Туре | Outdoor Projector |
| Designer | S.T. Fabas Luce |
| Eancode | 8019282507772 |
| Customs tariff | 94054239 |
| Color | Grey RAL 7040 |
| Material | Aluminum frame |
| IP | IP65 |
| IK | 07 |
| Insulation Class | |
| Operating ambient temperature | -20°C +50°C |
| Years of warranty | 5 |
| Made In | Italy |
| Item Dimensions | 384x123x319mm - 6.9kg |
| Packaging Dimensions | 420x420x170mm - 7.3kg |
| | Light Source 1 |
| Light source | LED Built-in |
| LED Characteristics | Power LED |
| Light Source Lumen | 18200 lm |
| Item Lumen | 16220 lm |
| Color Temperature | Natural white 4000 K |
| Optics | 90° |
| Minimum CRI | >80 |
| Luminous Flux Maintenance | 60.000h L70 B50 |
| Energy Efficiency Class | E |
| | Electrical specifications 1 |
| Input Voltage | 220 - 240V AC 50/60 Hz |
| Total Absorbed Power | 160W |
| Driver | Included |
| Power Factor | >0,9 |
| Control System | On/Off |





