




## Baku 30W

Fixed recessed appliance with 30W COB technology LED source. Aluminum body, reflector in polished metal with Darklight, Warm and Natural White emission, white finish. Electronic power supply On/Off, dimmable DALI or 0-10V included. Perfect for lighting offices and common or transit areas.

|                                      |   |
|--------------------------------------|---|
| <b>Code</b>                          | <b>6920-22-957</b>  |
| <b>Type</b>                          | Recessed lamp   |
| <b>Designer</b>                      | S.T. Fabas Luce   |
| <b>Eancode</b>                       | 8019282108726   |
| <b>Customs tariff</b>                | 94054239  |
| <b>Color</b>                         | White   |
| <b>Material</b>                      | Metal and polycarbonate frame   |
| <b>IP</b>                            | IP40  |
| <b>IK</b>                            | 08  |
| <b>Insulation Class</b>              |      |
| <b>Hole dimension</b>                |  175 |
| <b>Operating ambient temperature</b> | -20+35°C  |
| <b>Years of warranty</b>             | 5   |
| <b>Item Dimensions</b>               | 102mm Ø185mm - 0,80kg   |
| <b>Packaging Dimensions</b>          | 285x210x140mm - 1.2kg   |
| <b>Light Source 1</b>                |   |
| <b>Light source</b>                  | LED Built-in  |
| <b>LED Characteristics</b>           | COB   |
| <b>Number of LEDs</b>                | 1   |
| <b>Light Source Lumen</b>            | 3240 lm   |
| <b>Item Lumen</b>                    | 2325 lm   |
| <b>Color Temperature</b>             | Warm white 3000K  |
| <b>Optics</b>                        | 45°   |
| <b>Typical CRI</b>                   | >80   |
| <b>Minimum CRI</b>                   | >80   |
| <b>Luminous Flux Maintenance</b>     | >61.000h L80 B50  |
| <b>UGR</b>                           | <19   |
| <b>Energy Efficiency Class</b>       |    |
| <b>Electrical specifications 1</b>   |   |
| <b>Input Voltage</b>                 | 220 - 240V AC 50/60 Hz  |
| <b>Total Absorbed Power</b>          | 30W   |
| <b>Driver</b>                        | Included  |
| <b>Power Factor</b>                  | >0,9  |
| <b>Control System</b>                | 0-10V   |

