

Fabas Luce S.p.a. Via Luigi Talamoni 75, 20861 BRUGHERIO MB - ITALY Tel. +39 039 890691 Fax. +39 039 2142208 info@fabasluce.it - www.fabasluce.it

Toodle Asymmetrical round recessed

Small round recessed downlight in die-cast aluminum, designed to house COB 11W LEDs with high color rendering CRI> 90. Asymmetrical emission, supplied as standard with an opal diffuser for diffused emission. Ideal for residential lighting, waiting and transit areas. Available in White, Gold and Black finishes. Standard supplied with TRIAC power supply (DALI and Emergency kit on demand).

Code	6960-02-390	
Туре	Recessed lamp	
Designer	S.T. Fabas Luce	
Eancode	8019282509769	ANY COL
Customs tariff	94059900	
Color	Gold	The TANANS,
Material	Aluminum frame	
IP	IP40	
IK	06	
Insulation Class		
Hole dimension	72	
Operating ambient temperature	-20°C +45°C	
Years of warranty	3	
Item Dimensions	89mm Ø82mm - 0,30kg	ATT MATTIN
Packaging Dimensions	145x125x145mm - 0.45kg	
	Light Source 1	
Light source	LED Built-in	
LED Characteristics	СОВ	
Light Source Lumen	1250 lm	
Item Lumen	1050 lm	
Color Temperature	Warm white 3000K	
Optics	Asymmetric	
Typical CRI	92	Ø 82
Energy Efficiency Class		120° Germa Angles 180° 120°
	Electrical specifications 1	105°
Input Voltage	220 - 240V AC 50/60 Hz	90' 90'
Total Absorbed Power	11W	
Driver	Included	75°
Power Factor	>0,9	60' 1000 60'
Control System	Triac Dimm.	