




Kris Asymmetrical recessed with frame

Small square recessed downlight with asymmetrical emission. Die-cast aluminum body in version with frame and timeless, high color rendering LED CRI > 90. Ideal for residential lighting, waiting and transit areas. Available in Black and White finishes. Supplied as standard with TRIAC power supply (DALI and Emergency kit on demand).

Code	6961-02-461
Type	Recessed lamp
Designer	S.T. Fabas Luce
Eancode	8019282509981
Customs tariff	94059900
Color	Black
Material	Aluminum frame
IP	IP40
IK	05
Insulation Class	
Hole dimension	 99x99
Operating ambient temperature	-20°C +45°C
Years of warranty	3
Item Dimensions	106x106x58mm - 0,35kg
Packaging Dimensions	165x130x145mm - 0.5kg
	Light Source 1
Light source	LED Built-in
LED Characteristics	SMD
Light Source Lumen	930 lm
Item Lumen	687 lm
Color Temperature	Warm white 3000K
Optics	Asymmetric
Typical CRI	90
Energy Efficiency Class	
	Electrical specifications 1
Input Voltage	220 - 240V AC 50/60 Hz
Total Absorbed Power	8W
Driver	Included
Power Factor	>0,9
Control System	Triac Dimm.

