

Fabas Luce S.p.a. Via Luigi Talamoni 75, 20861 BRUGHERIO MB - ITALY Tel. +39 039 890691 Fax. +39 039 2142208 info@fabasluce.it - www.fabasluce.it

Kris Asymmetrical recessed with frame

Small square recessed downlight with asymmetrical emission. Die-cast aluminum body in version with frame and trimeless, high color rendering LED CRI>90. Ideal for residential lighting, waiting and transit areas. Available in Black and White finishes. Supplied as standard with TRIAC power supply (DALI and Emergency kit on demand).

| Code | 6961-04-461 | |
|-------------------------------|-----------------------------|------------------------|
| Туре | Recessed lamp | |
| Designer | S.T. Fabas Luce | |
| Eancode | 8019282510147 | |
| Customs tariff | 94059900 | |
| Color | Black | |
| Material | Aluminum frame | |
| IP | IP40 | |
| IK | 05 | |
| Insulation Class | | |
| Hole dimension | 99x99 | |
| Operating ambient temperature | -20°C +45°C | |
| Years of warranty | 3 | |
| Item Dimensions | 106x106x58mm - 0,35kg | |
| Packaging Dimensions | 165x130x145mm - 0.5kg | <u> </u> |
| | Light Source 1 | |
| Light source | LED Built-in | |
| LED Characteristics | SMD | 6 |
| Light Source Lumen | 950 lm | T 166 |
| Item Lumen | 752 lm | 2 |
| Color Temperature | Natural white 4000 K | 99x99 — |
| Optics | Asymmetric | |
| Typical CRI | 90 | |
| Energy Efficiency Class | A E E | 120° Gamma Angles 180° |
| | Electrical specifications 1 | 165* |
| Input Voltage | 220 - 240V AC 50/60 Hz | 90' |
| Total Absorbed Power | 8W | |
| Driver | Included | 75' |
| Power Factor | >0,9 | 60, 500 |
| Control System | Triac Dimm. | |
| | | 45' |