



## Millet Ceiling lamp

Extruded aluminum profile with cuts every 10 cm, with opal or prismatic polycarbonate diffuser UGR<19. Available in Warm 169 lm/W or Natural white 180 lm/W temperatures with mid power led 23W/m. Integrated power supply for On/Off and DALI power supplies, emergency module available on demand. Prepared to be installed on the ceiling or on the wall, both vertically and horizontally.

|                                      |   |
|--------------------------------------|---|
| <b>Code</b>                          | <b>6967-24-101</b>  |
| <b>Type</b>                          | Light Line Profiles – Ceiling lamp  |
| <b>Designer</b>                      | S.T. Fabas Luce   |
| <b>Eancode</b>                       | 8019282519546   |
| <b>Customs tariff</b>                | 94054239  |
| <b>Color</b>                         | Aluminum  |
| <b>Material</b>                      | Aluminum frame and polycarbonate  |
| <b>IP</b>                            | IP40  |
| <b>IK</b>                            | 08  |
| <b>Insulation Class</b>              |  |
| <b>Operating ambient temperature</b> | -25C° +45C°   |
| <b>Years of warranty</b>             | 5   |
| <b>Made In</b>                       | Italy   |
| <b>Item Dimensions</b>               | 46x70mm - 2,20m/kg  |

### Light Source 1

|                                  |   |
|----------------------------------|---|
| <b>Light source</b>              | LED Built-in  |
| <b>LED Characteristics</b>       | SMD   |
| <b>Number of LEDs</b>            | 80 LED/mt   |
| <b>Light Source Lumen</b>        | 3580 lm/m   |
| <b>Item Lumen</b>                | 2243 lm/m   |
| <b>Color Temperature</b>         | Natural white 4000 K  |
| <b>Optics</b>                    | Opal  |
| <b>Typical CRI</b>               | 85  |
| <b>Minimum CRI</b>               | 80  |
| <b>Luminous Flux Maintenance</b> | >100.000 h L80 B10  |
| <b>Energy Efficiency Class</b>   |  |

### Electrical specifications 1

|                             |                        |
|-----------------------------|------------------------|
| <b>Input Voltage</b>        | 220 - 240V AC 50/60 Hz |
| <b>Total Absorbed Power</b> | 23W/ml                 |
| <b>Driver</b>               | Included               |
| <b>Control System</b>       | On/Off                 |
| <b>Power Supply Type</b>    | Costant Current        |
| <b>Driver Output</b>        | 350mA                  |
| <b>Driver Input</b>         | 220 - 240 VAC 50/60 Hz |

