



Millet Ceiling lamp

Extruded aluminum profile with cuts every 10 cm, with opal or prismatic polycarbonate diffuser UGR<19. Available in Warm 169 lm/W or Natural white 180 lm/W temperatures with mid power led 23W/m. Integrated power supply for On/Off and DALI power supplies, emergency module available on demand. Prepared to be installed on the ceiling or on the wall, both vertically and horizontally.

| | |
|--------------------------------------|---|
| Code | 6967-62-101 |
| Type | Light Line Profiles – Ceiling lamp |
| Designer | S.T. Fabas Luce |
| Eancode | 8019282519539 |
| Customs tariff | 94054239 |
| Color | Black |
| Material | Aluminum frame and polycarbonate |
| IP | IP40 |
| IK | 08 |
| Insulation Class |  |
| Operating ambient temperature | -25C° +45C° |
| Years of warranty | 5 |
| Made In | Italy |
| Item Dimensions | 46x70mm - 2,20m/kg |

Light Source 1

| | |
|----------------------------------|---|
| Light source | LED Built-in |
| LED Characteristics | SMD |
| Number of LEDs | 80 LED/mt |
| Light Source Lumen | 3380 lm/m |
| Item Lumen | 2124 lm/m |
| Color Temperature | Warm white 3000K |
| Optics | Opal |
| Typical CRI | 85 |
| Minimum CRI | 80 |
| Luminous Flux Maintenance | >100.000 h L80 B10 |
| Energy Efficiency Class |  |

Electrical specifications 1

| | |
|-----------------------------|------------------------|
| Input Voltage | 220 - 240V AC 50/60 Hz |
| Total Absorbed Power | 23W/ml |
| Driver | Included |
| Control System | On/Off |
| Power Supply Type | Costant Current |
| Driver Output | 350mA |
| Driver Input | 220 - 240 VAC 50/60 Hz |

