



## Millet Suspension lamp

Extruded aluminium profile with 10 cm pitch cut-to-size, with opal or prismatic polycarbonate diffuser UGR<19. Available in 3000K or 4000K temperatures. Integrated for On/Off and DALI power supplies, emergency module available on request. Designed to be installed suspended, with L 2000 mm cable, other sizes on request.

|                                      |   |
|--------------------------------------|---|
| <b>Code</b>                          | <b>6968-62-101</b>  |
| <b>Type</b>                          | Light Line Profiles - Suspension lamp   |
| <b>Designer</b>                      | S.T. Fabas Luce   |
| <b>Eancode</b>                       | 8019282519805   |
| <b>Customs tariff</b>                | 94054239  |
| <b>Color</b>                         | Black   |
| <b>Material</b>                      | Aluminum frame and polycarbonate  |
| <b>IP</b>                            | IP40  |
| <b>IK</b>                            | 08  |
| <b>Insulation Class</b>              |  |
| <b>Operating ambient temperature</b> | -25C° +45C°   |
| <b>Years of warranty</b>             | 5   |
| <b>Made In</b>                       | Italy   |
| <b>Item Dimensions</b>               | 46x70xMAX 2000mm - 2.20/mkg   |

|                                  |   |
|----------------------------------|---|
| <b>Light Source 1</b>            |   |
| <b>Light source</b>              | LED Built-in  |
| <b>LED Characteristics</b>       | SMD   |
| <b>Number of LEDs</b>            | 80 LED/mt   |
| <b>Light Source Lumen</b>        | 3380 lm/m   |
| <b>Item Lumen</b>                | 2124 lm/m   |
| <b>Color Temperature</b>         | Warm white 3000K  |
| <b>Optics</b>                    | Opal  |
| <b>Typical CRI</b>               | 85  |
| <b>Minimum CRI</b>               | 80  |
| <b>Luminous Flux Maintenance</b> | >100.000 h L80 B10  |
| <b>Energy Efficiency Class</b>   |  |

|                                    |                        |
|------------------------------------|------------------------|
| <b>Electrical specifications 1</b> |                        |
| <b>Input Voltage</b>               | 220 - 240V AC 50/60 Hz |
| <b>Total Absorbed Power</b>        | 23W/ml                 |
| <b>Driver</b>                      | Included               |
| <b>Control System</b>              | On/Off                 |
| <b>Power Supply Type</b>           | Costant Current        |
| <b>Driver Output</b>               | 350 mA                 |
| <b>Driver Input</b>                | 220 - 240 VAC 50/60 Hz |

