




Millet Recessed frameless

Extruded aluminum profile with cuts every 10 cm., with opal or prismatic polycarbonate diffuser UGR<19. Available in Warm 169lm/W or Natural white 180lm/W temperatures with mid power led 23/Wm. Integrated power supply for On/Off and DALI power supplies, emergency module available on demand.

Code	6971-52-202
Type	Light Line Profiles – Recessed frameless
Designer	S.T. Fabas Luce
Eancode	8019282520368
Customs tariff	94054239
Color	White
Material	Aluminum frame and polycarbonate
IP	IP40
IK	08
Insulation Class	
Hole dimension	 52 X L + 20
Operating ambient temperature	-25C° +45C°
Years of warranty	5
Item Dimensions	46x122mm - 2,2/mkg
Light Source 1	
Light source	LED Built-in
LED Characteristics	SMD
Number of LEDs	80 LED/mt
Light Source Lumen	3380 lm/m
Item Lumen	2196 lm/m
Color Temperature	Warm white 3000K
Optics	Prismatic
Typical CRI	85
Minimum CRI	80
Luminous Flux Maintenance	>100.000 h L80 B10
UGR	<19
Energy Efficiency Class	
Electrical specifications 1	
Input Voltage	220 - 240V AC 50/60 Hz
Total Absorbed Power	23W/ml
Driver	Included
Control System	On/Off
Power Supply Type	Costant Current
Driver Output	350mA
Driver Input	220 - 240 VAC 50/60 Hz

