



## Rubens 16W

Adjustable floodlight with adapter for installation on a track, mains voltage for 16W LED source with high efficiency available in Warm or Natural White shades. Excellent color rendering with COB REAL COLOR CRI 97. Built-in electronic ballast in On/Off or DALI versions. The luminaire is made of die-cast aluminum and thermoplastic material, it allows a rotation of 350° around the vertical axis and an inclination of 90° with respect to the horizontal plane. Available in white or black in 15°, 28°, 41° optics.

|                                      |   |
|--------------------------------------|---|
| <b>Code</b>                          | <b>6973-92-566</b>  |
| <b>Type</b>                          | Track spotlight   |
| <b>Designer</b>                      | S.T. Fabas Luce   |
| <b>Eancode</b>                       | 8019282527343   |
| <b>Customs tariff</b>                | 94054239  |
| <b>Color</b>                         | Black   |
| <b>Material</b>                      | Aluminum frame  |
| <b>IP</b>                            | IP20  |
| <b>IK</b>                            | 04  |
| <b>Insulation Class</b>              |  |
| <b>Operating ambient temperature</b> | -20°C + 35°C  |
| <b>Years of warranty</b>             | 5   |
| <b>Made In</b>                       | Italy   |
| <b>Item Dimensions</b>               | 95mm Ø55mm - 0.38kg   |
| <b>Packaging Dimensions</b>          | 200x165x70mm - 0.52kg   |

### Light Source 1

|                                  |   |
|----------------------------------|---|
| <b>Light source</b>              | LED Built-in  |
| <b>LED Characteristics</b>       | COB   |
| <b>Light Source Lumen</b>        | 1260 lm   |
| <b>Item Lumen</b>                | 881 lm  |
| <b>Color Temperature</b>         | Warm white 3000K  |
| <b>Optics</b>                    | 41°   |
| <b>Typical CRI</b>               | 97  |
| <b>Minimum CRI</b>               | 90  |
| <b>Luminous Flux Maintenance</b> | 50.000h L80 B10   |
| <b>Energy Efficiency Class</b>   |  |

### Electrical specifications 1

|                             |                        |
|-----------------------------|------------------------|
| <b>Input Voltage</b>        | 220 - 240V AC 50/60 Hz |
| <b>Total Absorbed Power</b> | 16W                    |
| <b>Driver</b>               | Included               |
| <b>Power Factor</b>         | >0,9                   |
| <b>Control System</b>       | DALI                   |

