

Fabas Luce S.p.a. Via Luigi Talamoni 75, 20861 BRUGHERIO MB - ITALY Tel. +39 039 890691 Fax. +39 039 2142208 info@fabasluce.it - www.fabasluce.it

Rubens 16W

Adjustable floodlight with adapter for installation on a track, mains voltage for 16W LED source with high efficiency available in Warm or Natural White shades. Excellent color rendering with COB REAL COLOR CRI 97. Built-in electronic ballast in On/Off or DALI versions. The luminaire is made of diecast aluminum and thermoplastic material, it allows a rotation of 350° around the vertical axis and an inclination of 90° with respect to the horizontal plane. Available in white or black in 15°, 28°, 41° optics.

Code	6973-94-354	
Туре	Track spotlight	
Designer	S.T. Fabas Luce	
Eancode	8019282527183	
Customs tariff	94054239	
Color	White	Jean Land
Material	Aluminum frame	
IP	IP20	
IK	04	0
Insulation Class		
Operating ambient temperature	-20°C + 35°C	
Years of warranty	5	
Made In	Italy	
Item Dimensions	95mm Ø55mm - 0.38kg	-
Packaging Dimensions	200x165x70mm - 0.52kg	
	Light Source 1	
Light source	LED Built-in	350°
LED Characteristics	СОВ	90°
Light Source Lumen	1312 lm	
Item Lumen	1134 lm	
Color Temperature	Natural white 4000 K	
Optics	28°	055
Typical CRI	97	- 35
Minimum CRI	90	
Luminous Flux Maintenance	50.000h L80 B10	- 120° Gamma Angles 180° 120°
Energy Efficiency Class	[↑ G D	100 USINIII A MUIDO 100 120 105° 105°
	Electrical specifications 1	90° 90°
Input Voltage	220 - 240V AC 50/60 Hz	
Total Absorbed Power	16W	5* 800 75*
Driver	Included	60° 60°
Power Factor	>0,9	200
Control System	On/Off	45°