



Rubens 28W

Adjustable floodlight with adapter for installation on a track, mains voltage for 28W LED source with high efficiency available in Warm or Natural White shades. Excellent color rendering with COB REAL COLOR CRI 97. Built-in electronic ballast in On/Off or DALI versions. The luminaire is made of die-cast aluminum and thermoplastic material, it allows a rotation of 350° around the vertical axis and an inclination of 90° with respect to the horizontal plane. Available in white or black in 16°, 21°, 43° optics.

| | |
|--------------------------------------|---|
| Code | 6974-92-554 |
| Type | Track spotlight |
| Designer | S.T. Fabas Luce |
| Eancode | 8019282527510 |
| Customs tariff | 94054239 |
| Color | White |
| Material | Aluminum frame |
| IP | IP20 |
| IK | 04 |
| Insulation Class |  |
| Operating ambient temperature | -20°C + 35°C |
| Years of warranty | 5 |
| Item Dimensions | 118mm Ø70mm - 0.59kg |
| Packaging Dimensions | 90x210x210mm - 0.74kg |
| Light Source 1 | |
| Light source | LED Built-in |
| LED Characteristics | COB |
| Light Source Lumen | 2600 lm |
| Item Lumen | 1930 lm |
| Color Temperature | Warm white 3000K |
| Optics | 43° |
| Typical CRI | 97 |
| Minimum CRI | 90 |
| Luminous Flux Maintenance | 50.000h L80 B10 |
| Energy Efficiency Class |  |
| Electrical specifications 1 | |
| Input Voltage | 220 - 240V AC 50/60 Hz |
| Total Absorbed Power | 28W |
| Driver | Included |
| Power Factor | >0,9 |
| Control System | On/Off |

