



Rubens 36W

Adjustable floodlight with adapter for installation on a track, mains voltage for 36W LED source with high efficiency available in Warm or Natural White shades. Excellent color rendering with COB REAL COLOR CRI 97. Built-in electronic ballast in On/Off or DALI versions. The luminaire is made of die-cast aluminum and thermoplastic material, it allows a rotation of 350° around the vertical axis and an inclination of 90° with respect to the horizontal plane. Available in white or black in 21°, 36°, 45° optics.

| | |
|--------------------------------------|---|
| Code | 6975-92-356 |
| Type | Track spotlight |
| Designer | S.T. Fabas Luce |
| Eancode | 8019282527930 |
| Customs tariff | 94054239 |
| Color | White |
| Material | Aluminum frame |
| IP | IP20 |
| IK | 04 |
| Insulation Class |  |
| Operating ambient temperature | -20°C +35°C |
| Years of warranty | 5 |
| Item Dimensions | 132mm Ø85mm - 0.8kg |
| Packaging Dimensions | 90x210x210mm - 0.92kg |
| Light Source 1 | |
| Light source | LED Built-in |
| LED Characteristics | COB |
| Light Source Lumen | 3800 lm |
| Item Lumen | 2758 lm |
| Color Temperature | Warm white 3000K |
| Optics | 36° |
| Typical CRI | 97 |
| Minimum CRI | 90 |
| Luminous Flux Maintenance | 50.000h L80 B10 |
| Energy Efficiency Class |  |
| Electrical specifications 1 | |
| Input Voltage | 220 - 240V AC 50/60 Hz |
| Total Absorbed Power | 36W |
| Driver | Included |
| Power Factor | >0,9 |
| Control System | DALI |

