



## Manet 300x1200

Direct emission ceiling lamp for recessed installation, standin or ceiling-mounted with special accessory. Optical compartment in painted metal, UGR<19 microprismatic shield, Mid power LED 40W high yield CRI 90. White finish, Warm and Natural White. Electronic power supply On/Off, dimmable DALI o 0-10V included. Emergency kit on demand. Perfect for lighting offices, open spaces and for generale lighting in large areas.

<b>Code</b>	<b>6981-04-755</b>
<b>Type</b>	Recessed lamp
<b>Designer</b>	S.T. Fabas Luce
<b>Eancode</b>	8019282530718
<b>Customs tariff</b>	94054239
<b>Color</b>	White
<b>Material</b>	Metal frame / Clear prismatic diffuser
<b>IP</b>	IP40
<b>IK</b>	05
<b>Insulation Class</b>	
<b>Operating ambient temperature</b>	-20°C +45°C
<b>Years of warranty</b>	5
<b>Item Dimensions</b>	1195x295x62mm - 3,00kg
<b>Packaging Dimensions</b>	1122x370x90mm - 3.9kg

### Light Source 1

<b>Light source</b>	Built-in
<b>LED Characteristics</b>	SMD
<b>Number of LEDs</b>	210
<b>Light Source Lumen</b>	5500 lm
<b>Color Temperature</b>	Natural white 4000 K
<b>Optics</b>	Prismatic
<b>Typical CRI</b>	> 90
<b>Luminous Flux Maintenance</b>	>54.000h L70 B50
<b>UGR</b>	<19
<b>Energy Efficiency Class</b>	

### Electrical specifications 1

<b>Input Voltage</b>	220 - 240V AC 50/60 Hz
<b>Total Absorbed Power</b>	40W
<b>Driver</b>	Included
<b>Power Factor</b>	> 0.9
<b>Control System</b>	DALI/Push

