



## Manet IP55 600x600

Direct emission ceiling lamp IP55 for recessed installation or ceiling-mounted with special accessory. Optical compartment in painted metal, UGR<19 microprismatic shield, Mid power LED 40W high yield CRI 90. White finish, Warm and Natural White. Electronic power supply On/Off, dimmable DALI or 0-10V included. Emergency kit on demand. IP55 version is perfect for lighting offices, open spaces and for general lighting in large areas.

<b>Code</b>	<b>6982-04-065</b>
<b>Type</b>	Recessed lamp
<b>Designer</b>	S.T. Fabas Luce
<b>Eancode</b>	8019282525462
<b>Customs tariff</b>	94054239
<b>Color</b>	White
<b>Material</b>	Metal frame / Clear prismatic diffuser
<b>IP</b>	IP55
<b>IK</b>	05
<b>Insulation Class</b>	
<b>Operating ambient temperature</b>	-20°C +45°C
<b>Years of warranty</b>	5
<b>Item Dimensions</b>	595x595x61mm - 3.0kg
<b>Packaging Dimensions</b>	610x660x90mm - 3.7kg
<b>Light Source 1</b>	
<b>Light source</b>	LED Built-in
<b>LED Characteristics</b>	SMD
<b>Light Source Lumen</b>	5500 lm
<b>Item Lumen</b>	4347 lm
<b>Color Temperature</b>	Natural white 4000 K
<b>Optics</b>	Prismatic
<b>Minimum CRI</b>	>90
<b>Luminous Flux Maintenance</b>	>54.000 L70 B50
<b>UGR</b>	<19
<b>Energy Efficiency Class</b>	
<b>Electrical specifications 1</b>	
<b>Input Voltage</b>	220 - 240V AC 50/60 Hz
<b>Total Absorbed Power</b>	40W
<b>Driver</b>	Included
<b>Power Factor</b>	> 0.9
<b>Control System</b>	0-10V

