



## Manet 300x1200

Direct emission ceiling lamp for recessed stand-in. Optical compartment in painted metal, UGR<19 microprismatic shield, Mid power LED 40W high yield CRI 90. White finish, Warm and Natural White. Electronic power supply On/Off, dimmable DALI o 0-10V included. Emergency kit on demand. Perfect for lighting offices, open spaces and for general lighting in large areas.

|                                      |   |
|--------------------------------------|---|
| <b>Code</b>                          | <b>6988-02-765</b>  |
| <b>Type</b>                          | Recessed lamp   |
| <b>Designer</b>                      | S.T. Fabas Luce   |
| <b>Eancode</b>                       | 8019282530596   |
| <b>Customs tariff</b>                | 94054239  |
| <b>Color</b>                         | White   |
| <b>Material</b>                      | Metal frame / Clear prismatic diffuser  |
| <b>IP</b>                            | IP40  |
| <b>IK</b>                            | 05  |
| <b>Insulation Class</b>              |  |
| <b>Operating ambient temperature</b> | -20°C +45°C   |
| <b>Years of warranty</b>             | 5   |
| <b>Item Dimensions</b>               | 300x1200x62mm - 3,20kg  |
| <b>Packaging Dimensions</b>          | 1122x370x90mm - 4.2kg   |

### Light Source 1

|                                  |   |
|----------------------------------|---|
| <b>Light source</b>              | Built-in  |
| <b>LED Characteristics</b>       | SMD   |
| <b>Number of LEDs</b>            | 210   |
| <b>Light Source Lumen</b>        | 5100 lm   |
| <b>Color Temperature</b>         | Warm white 3000K  |
| <b>Optics</b>                    | Prismatic   |
| <b>Typical CRI</b>               | > 90  |
| <b>Luminous Flux Maintenance</b> | >54.000h L70 B50  |
| <b>UGR</b>                       | <19   |
| <b>Energy Efficiency Class</b>   |  |

### Electrical specifications 1

|                             |                        |
|-----------------------------|------------------------|
| <b>Input Voltage</b>        | 220 - 240V AC 50/60 Hz |
| <b>Total Absorbed Power</b> | 40W                    |
| <b>Driver</b>               | Included               |
| <b>Power Factor</b>         | > 0.9                  |
| <b>Control System</b>       | 0-10V                  |

