



Kate IP65

Round polycarbonate and aluminum profile, Ø25 mm, for outdoor direct illumination of rooms, walls and objects. Fixing with adjustable springs, 360° rotation, dull chrome brackets on demand. Provided wired with a 1 m neoprene cable. IP65 protection rating. Customized product cut each 10 cm.

| | |
|--------------------------------------|---|
| Code | 6996-04-001 |
| Type | Light Line Profiles |
| Designer | S.T. Fabas Luce |
| Eancode | 8019282534730 |
| Customs tariff | 94054239 |
| Color | Shiny anodized aluminum |
| Material | Aluminum frame |
| IP | IP65 |
| IK | 08 |
| Insulation Class |  |
| Operating ambient temperature | -20°C +50°C |
| Years of warranty | 3 |
| Made In | Italy |
| Item Dimensions | Ø250mm - 0,75/mkg |
| Light Source 1 | |
| Light source | LED Built-in |
| LED Characteristics | SMD |
| Number of LEDs | 160 LED/mt |
| Light Source Lumen | 2800 lm/m |
| Item Lumen | 1550 lm/m |
| Color Temperature | Natural white 4000 K |
| Optics | 120°-120° opal - 60° |
| Minimum CRI | >80 |
| Energy Efficiency Class |  |
| Electrical specifications 1 | |
| Input Voltage | 24V DC |
| Total Absorbed Power | 20W/ml |
| Driver | Not included |

