



Nizza

High efficiency floodlight for functional and architectural lighting. Suitable especially for outdoor areas. It has a wide range of optics to meet all design needs. Device made of die-cast aluminum copper free EN AB 44100. Polyester painting QUALICOAT (Class 1), corrosion resistant to salt spray for 28 days, conforms to Standard IEC60092-306. Available in grey color RAL 7040, INOX brackets.

Code	6876-04-424
Type	Projecteur extérieur
Designer	S.T. Fabas Luce
Code Barres	8019282103011
Tarif douanier	94054239
Couleur	aluminium anodisé brillant
Matériel	Monture en aluminium
IP	IP66
IK	08
Classe d'isolation	
Operating ambient temperature	-25°C +50°C
Ans de garantie	5
Made In	Italy
Dimensions de la lampe	400x100x170,50mm - 2,60kg
Dimensions de la boîte	485x125x190mm - 2.9kg
	Source de lumière 1
Source	LED Intégré
Caractéristiques des LEDs	Power LED
Lumens de la source lumineuse	6700 lm
Lumen de l'article	4780 lm
Température de couleur	Natural white 4000 K
Optique	Elliptical
CRI minimum	>80
Maintien du flux lumineux	60.000h L70 B50
Classe énergétique	
	Spécifications électriques 1
Tension d'alimentation	100 - 240V AC 50/60 Hz
Puissance totale absorbée	54W
Driver	Inclus
Facteur de puissance	>0,9
Système de contrôle	On/Off

